

Performance

SPEC.(mm)		500H	600H	700H	800H	900H	1000H	1100H	1150H	1200H	1300H	1400H	1600H	1800H	2000H
PERFORMANCE															
RS	R	340	480	655	862	1078	1339	1490	1764	1760	2125	2255	3130	3750	4260
	E	80	155	232	368	480	669	840	1029	1110	1585	1686	2420	3530	4630
	R	270	382	525	706	862	1078	1150	1395	1400	1705	1804	2268	3000	3540
	E	65	125	180	294	395	541	650	880	880	1310	1349	1935	2830	3800
RH	R	195	285	380	510	640	785	930	1050	1120	1340	1445	1815	2400	2980
	E	46	94	150	225	310	435	495	660	710	1043	1079	1548	2260	3190
	R	465	230	310	410	510	630	800	830	890	1125	1150	1420	1910	2655
	E	37	75	120	180	252	350	408	530	560	750	860	1230	1800	2830
RO	R	340	480	655	862	1078	1339	1490	1764	1760	2125	2255	3130	3750	4260
	E	80	155	232	368	480	669	840	1029	1110	1585	1686	2420	3530	4630
	R	270	382	525	706	862	1078	1150	1395	1400	1705	1804	2268	3000	3540
	E	65	125	180	294	395	541	650	880	880	1310	1349	1935	2830	3800
RL	R	195	285	380	510	640	785	930	1050	1120	1340	1445	1815	240	2980
	E	46	94	150	225	310	435	495	660	710	1043	1079	1548	2260	3190
	R	165	230	310	410	510	630	800	830	890	1125	1150	1420	1910	2655
	E	37	75	120	180	252	350	408	530	560	750	860	1230	1800	2830
RS: Super high Reaction Force RH: High Reaction Force RO: Standard Reaction Force RL: Low Reaction Force							R: Reaction Force E: Energy Absorption Rated Deflection: 70% Performance tolerance: $\pm 10\%$								